HVAC PUMPS PRIMARY CHILLED WATER PUMPS P1 & P2

Quantity: 2 each

Brand: Weinman

Type: Frame Mounted End Suction, Flanged Connection

Model: 4G-2A

Fluid: Chilled water @ 44 F

GPM: 432

TDH: 34 feet Discharge position:

Materials of construction: Standard fitted

With mechanical seals

Premiun Efficiency Motor

HP: 5

RPM: 1750

Phases: 3

Volts: 230/460

Hertz: 60 Frame: 184T

With Kynar separators

With shaft coupling guard

HVAC PUMPS CONDENSER WATER PUMPS P4 & P5

Quantity: 2 each

Brand: Weinman

Type: Frame Mounted End Suction, Flanged Connection

Model: 4K-4A

Fluid: Water @ 95 F

GPM: 540

TDH: 115 feet Discharge position:

Materials of construction: Standard fitted

With mechanical seals

Premiun Efficiency Motor

HP: 30 RPM: 1750 Phases: 3 Volts: 230/460

Hertz: 60 Frame: 286T

With Kynar separators
With shaft coupling guard

HVAC PUMPS SECONDARY CHILLED WATER PUMPS P7 & P8

Quantity: 2 each

Brand: Weinman

Type: Frame Mounted End Suction, Flanged Connection

Model: 4KL-4A

Fluid: Chilled water @ 44 F

GPM: 683

TDH: 54.5 feet Discharge position:

Materials of construction: Standard fitted

With mechanical seals

Premiun Efficiency Motor

HP: 15
RPM: 1750
Phases: 3
Volts: 230/460

Hertz: 60 Frame: 254T

With Kynar separators
With shaft coupling guard

HVAC PUMPS SECONDARY WATER PUMPS P9 & P10

Quantity: 2 each

Brand: Weinman

Type: Frame Mounted End Suction, Flanged Connection

Model: 3KH-4A

Fluid: Water @ 95 F

GPM: 305.7

TDH: 130 feet Discharge position:

Materials of construction: Standard fitted

With mechanical seals

Premiun Efficiency Motor

HP: 20 RPM: 1750

Phases: 3 Volts: 230/4

Volts: 230/460 Hertz: 60 Frame: 256T

With Kynar separators

With shaft coupling guard

.